## List of Contents

### NUMBER 1


| | | |
|---|---|---|
| **E. Altus** and **A. Dorogoy** | 1 | A three-dimensional study of delamination |
| **M. Sarfarazi** | 21 | Micromechanical evaluation of microplastic strains prior to microfracture in polycrystalline solids |
| **T. Y. Kam** and **C. D. Lu** | 37 | Reliability analysis of brittle systems considering several random variables |
| **I. D. Parsons** and **J. F. Hall** | 45 | A finite element investigation of the elastostatic state near a three dimensional edge crack |
| **Ramesh Chandra** | 65 | Experimental determination of stress intensity factors in patched cracked plates |
| **M. Heller, R. Jones** and **J. F. Williams** | 81 | Numerical analysis of bonded repairs for fastener holes with three-dimensional cracks |
| **J. Heitzer** and **C. Mattheck** | 91 | FEM-calculation of the stress intensity factors of a circular arc crack under uniaxial tension |
| **Kong Xian-Ming, Zheng Si-Tao** and **Cui Zhen-Yuan** | 105 | Studies on stress intensity factor $K_I$ of surface cracks in a cylinder under remote tension loads |
| **V. K. Srivastava** | 113 | Effect of filler on fracture of short glass fibre reinforced epoxy resin |
| **M. S. Cayard** and **W. L. Bradley** | 121 | A comparison of several analytical techniques for calculating $J$–$R$ curves from load–displacement data and their relation to specimen geometry |
| **Xiaolie Chen** and **Keijiro Nakasa** | 133 | Effect of mixed mode loading on the crack propagation direction in hydrogen assisted cracking |
| **P. C. Bastias, G. T. Hahn** and **C. A. Rubin** | 143 | Finite element modelling of subsurface mode II cracks under contact loads |
| | | *Technical Note* |
| **J. D. G. Sumpter** | 153 | A quick method for $J_c$ determination |
| | I | Software Survey Section |


### NUMBER 2


| | | |
|---|---|---|
| **F. F. Mahmoud** and **A. G. El Shafei** | 157 | A direct automated procedure for frictionless thermo-elastic contact problems |

| | | |
|---|---|---|
| **J. S. Short** and **D. W. Hoeppner** | 165 | The maximal dissipation rate criterion—I. Hypothesis and theoretical considerations |
| **J. S. Short** and **D. W. Hoeppner** | 175 | A global/local theory of fatigue crack propagation |
| **P. S. Theocaris** | 185 | The elliptic paraboloid failure surface for 2D-transtropic plates (fiber laminates) |
| **P. S. Theocaris** | 205 | Variations on the theme of fracture criteria |
| **O. Kolednik** and **P. Kutleša** | 215 | On the influence of specimen geometry on the critical crack-tip-opening displacement |
| **N. Hasebe, M. Miwa** and **T. Nakamura** | 225 | Stress analysis of a crack at a juncture of a strip and a half-plane |
| **R. C. McClung** and **H. Sehitoglu** | 237 | On the finite element analysis of fatigue crack closure —1. Basic modeling issues |
| **R. C. McClung** and **H. Sehitoglu** | 253 | On the finite element analysis of fatigue crack closure —2. Numerical results |
| **Wei Shen, Li-Hua Peng, Yun-Guo Yue, Zeng Shen** and **Xian-Dong Tang** | 273 | Elastic damage and energy dissipation in anisotropic solid material |
| **G. A. Papadopoulos** | 283 | New concepts on the Det.-criterion |
| **Y. Nakajima, Y. Iino** and **M. Suzuki** | 295 | Fracture toughness behaviour of service-exposed type 321 stainless steel at room and elevated temperature under normal and low straining rates |
| **J. Wang** and **C. L. Chow** | 309 | Subcritical crack growth in ductile fracture with continuum damage mechanics |
| | I | Software Survey Section |


**NUMBER 3**


| | | |
|---|---|---|
| **X. S. Zhang** | 319 | Transient response of an edge crack in a rectangular plate with stress-free edges for the tearing mode |
| **X. S. Zhang** | 327 | A central crack at the interface between two different orthotropic media for the mode I and mode II |
| **P. S. Theocaris** | 335 | Decomposition of strain energy density in fiber reinforced composites |
| **P. S. Theocaris** and **C. Lazopoulos** | 345 | Further properties of reflected caustics for solving problems with several unknowns |
| **R. Sethuraman** and **S. K. Maiti** | 355 | Determination of mixed mode stress intensity factors for a crack-stiffened panel |

| | | |
|---|---|---|
| **Huseyin Sehitoglu** and **Wei Sun** | 371 | The significance of crack closure under high temperature fatigue crack growth with hold periods |
| **D. J. Quesnel** and **R. W. Bush** | 389 | The destabilizing influence of plastic yielding on fracture |
| **Y. Z. Itoh, S. Suruga** and **H. Kashiwaya** | 397 | Prediction of fatigue crack growth rate in welding residual stress field |
| **C. Vipulanandan** and **N. Dharmarajan** | 409 | Critical crack tip opening displacement for polymer composites |
| **S. A. Hamoush** and **S. H. Ahmad** | 421 | Mode I and mode II stress intensity factors for interfacial cracks in bi-material media |
| **Fred Nilsson, Patrich Ohlsson, Fredrik Sjöberg** and **Per Ståhle** | 429 | A strip-yield rate-dependent model for rapid loading conditions |
| **K. Badarinarayana** and **K. S. S. Aradhya** | 437 | On the investigation of singular stress field around radial cracks in annulii subjected to diametrical tension |
| **K. S. S. Aradhya, K. Badarinarayana** and **L. S. Srinath** | 445 | Mixed-mode stress intensity factors for arbitrarily oriented cracks in cylindrical shells under axial pull and torsion |
| **K. S. Chan** and **D. L. Davidson** | 451 | Driving forces for composite interface fatigue cracks |
| **Chiaki Ihara, Tetsuya Misawa** and **Yosihide Shigeyama** | 467 | A stochastic approach to fatigue damage of carbon fiber composites |
| **N. C. Huang** and **Y. C. Li** | 477 | Steady fatigue crack growth under tensile load |
| | | *Technical Note* |
| **Ji-Liang Doong, Tsyr-Jang Chen** and **Yen-Hung Tan** | 483 | Effect of laser surface hardening on fatigue crack growth rate in AISI-4130 steel |
| | I | Software Survey Section |


**NUMBER 4**


| | | |
|---|---|---|
| **Chen Yi-Heng** and **Shen Ya-Peng** | 493 | Solution of multiple transverse crack problems in anisotropic sheets and composite laminates |
| **X. S. Zhang** | 509 | A tearing mode crack located anywhere in a finite rectangular sheet |
| **X. S. Zhang** | 517 | The problems of a concentric penny-shaped crack at the interface between two transversely isotropic media in an infinite cylinder |

| | | |
|---|---|---|
| **I. S. Raju** and **W. B. Fichter** | 525 | A finite-element alternating method for two dimensional mode I crack configurations |
| **G. M. Newaz** and **J. Ahmad** | 541 | A simple technique for measuring mode I delamination energy release rate in polymeric composites |
| **P. S. Theocaris** | 553 | Definition of the crack tip as the center of the caustic |
| **F. W. Brust, M. Nakagaki** and **C. Springfield** | 561 | Integral parameters for thermal fracture |
| **Zhang Yongyuan, Luo Gangming** and **Wang Yongjian** | 581 | Investigation of a column with a slant elliptic crack under compression in boundary element method |
| **R. Paskaramoorthy, A. H. Shah** and **S. K. Datta** | 589 | Scattering of flexural waves by a crack in a plate |
| **E. Smith** | 599 | The effect of a kink, a U-loop and a T-junction on the instability of a circumferential through-wall crack in a stainless steel piping system |
| **G. J. Rodin** and **Yuh-Long Hwang** | 611 | The penny-shaped crack in an infinite body of a power-law material subjected to remote shear |
| **G.-P. Fang, R. A. Schapery** and **Y. Weitsman** | 619 | Thermally-induced fracture in composites |
| **Y. Blanchette, J. I. Dickson** and **J. P. Bailon** | 633 | Influence of simultaneously occurring brittle cracking on ductile fatigue crack growth rates—Part I. Modelling of the semi-cohesive zone |
| **Y. Blanchette, J. P. Bailon** and **J. I. Dickson** | 643 | Influence of simultaneously occurring brittle cracking on ductile fatigue crack growth rates—Part II. Comparison of experimental results with model predictions |
| **B. N. Cox** | 655 | Inductions from Monte Carlo simulations of small fatigue cracks |
| | I | Software Survey Section |


**NUMBER 5**


| | | |
|---|---|---|
| **K. S. Zhang, L. S. Hua, C. Q. Zheng** and **J. C. Radon** | 671 | A computer simulation of ductile fracture initiation in TPB specimen—an application of $V_{gc}$ criterion |
| **L. Stagni** | 679 | Line singularity near the tip of a crack and of a fixed rigid line: unified treatment |
| **Zheng Xiulin** | 685 | On an unified model for predicting notch strength and fracture toughness of metals |
| **S. T. Shiue, C. T. Hu** and **Sanboh Lee** | 697 | Elastic interaction between screw dislocations and a welded surface crack in composite materials |

| | | |
|---|---|---|
| **P. S. Theocaris** | 707 | The topography around an internal crack: differences between exact and two-term solutions |
| **P. S. Theocaris** and **T. P. Philippidis** | 719 | The exact modes of formation of near-field reflected caustics |
| **G. Jayarama Rao** and **R. Narayanan** | 733 | Photoelastic analysis of mode I stress intensity factor by two-parameter methods |
| **L. Schovanec** and **W. T. Timmons** | 745 | Some aspects of crack behavior in a nonhomogeneous material |
| **M. A. Awal, T. Kundu** and **S. P. Joshi** | 753 | Dynamic behavior of delamination and transverse cracks in fiber reinforced laminated composites |
| **S. Swaddiwudhipong, C.-Y. Liaw** and **K.-L. Cheng** | 765 | Fatigue crack growth and failure of tubular members |
| **V. G. DeGiorgi, G. C. Kirby III** and **M. I. Jolles** | 773 | Prediction of classical fracture initiation toughness |
| **H. Tanaka** and **A. Tsurui** | 787 | Random propagation of a semi-elliptical surface crack as a bivariate stochastic process |
| **M. Kamaraj** and **V. M. Radhakrishnan** | 801 | High temperature crack growth in austenitic weld metal |
| **O. Kolednik** | 813 | An improved procedure for calculating COD in bend and CT specimens |
| | | *Letter to the Editor* |
| **W. R. Tyson** and **G. Roy** | 827 | Are the foundations of fracture mechanics cracked? |
| | | *Technical Note* |
| **F. M. Furgiuele** and **M. L. Luchi** | 831 | A note on some crack tip elements employed in two-dimensional elasto-plastic fracture mechanics |
| | I | Software Survey Section |

**NUMBER 6**

| | | |
|---|---|---|
| **Steven G. Russell** | 839 | A new model for fatigue crack growth retardation following an overload |
| **R. J. Dexter, S. J. Hudak, Jr** and **D. L. Davidson** | 855 | Modelling and measurement of crack closure and crack growth following overloads and underloads |
| **S. Sahraoui** and **F. Gillaizeau** | 871 | Numerical simulation of the Charpy impact testing |
| **X. R. Wu** and **X. G. Chen** | 877 | Wide-range weight function for center cracks |
| **Chen Yi-Heng** and **Hans-Georg Hahn** | 887 | Interaction of a stiffener with a crack in an anisotropic sheet |

| | | |
|---|---|---|
| **O. Haber, H. Grebner** and **A. Höfler** | 897 | Application of conformal mapping for mesh generation in two-dimensional elasto-plastic fracture mechanics problems |
| **J. Xie** and **Y. W. Shi** | 907 | Effect of yield stress and specimen size on the position of fracture toughness peak (FTP) in $J_i$–$a/W$ curves |
| **D. A. Meyn, T. W. Webb** and **E. C. Aifantis** | 913 | Hydrogen-assisted cracking studies of 4340 steel by using the optical method of caustics |
| **D. W. A. Rees** | 927 | Fatigue crack growth in thick-walled cylinders under pulsating internal pressure |
| **A. Bhattacharya** | 941 | Rigid body rotation surrounding the mode II crack |
| **Dragoslav Sumarac** and **Dusan Krajcinovic** | 949 | A simple solution for a crack reinforced by bands |
| **D. L. Davidson** | 965 | The growth of fatigue cracks through particulate SiC reinforced aluminum alloys |
| **Hao Tian-Hu** and **Wu Yong-Chang** | 979 | Elastic plane problem of collinear periodical rigid lines |
| **Y. Z. Chen** | 983 | Weight function technique in a more general case |
| | I | Software Survey Section |